



Model DT CR

600 L
800 L
1000 L
1500 L
2000 L



Prednosti pršilnikov DT CR:

- dva ventilatorja ki se vrtita v nasprotno smer
- simetričen izstop zraka na levi in desni strani
- zaradi posebne izvedbe usmernika, se zrak vrtniči takoj po izstopu iz usmernika
- dvojni nosilci šob z membranskimi proti kapnimi ventili se lahko prestavljajo po višini
- velika vlivna odprtina z mešalcem prašnatih sredstev
- čistilec rezervoarja
- daljinska komanda z električnimi membranskimi ventili
- premična ruda, ki sledi koloteku traktorja
- luči za vožnjo po cesti



Dodatna oprema:

- električna regulacija tlaka
- zapiranje v več sekcijah
- vklop šob s pomočjo senzorjev
- računalnik za škropljenje
- čistilec embalaže
- osvetlitev šob z LED diodami



Vorteile der Gebläsespritzen DT CR:

- Mit Umkehrgetriebe und zwei gegenläufige Ventilatoren
- Symmetrisches Luftaustritt an linke und rechte Seite
- Durch das Bi- Strahlsystem entsteht schon vor der Kulturreihe eine starke Luftverwirbelung
- Doppelschwenkdüsen mit Membranabsperrenten, die in der Höhe verstellbar sind
- Fernbedienung mit Elektromembranventilen
- Große Einfüllöffnung mit Einspülvorrichtung
- Behälter-Innenreinigung
- Knickdeichsel
- Beleuchtung

Wunschausrüstung:

Elektroventile, Kanisterreiniger, Computersteuerung, Sensortechnik, Düsenbeleuchtung mit LED ...



Sprayers DT CR have following advantages:

- Two contra rotated ventilators
- Symmetric output of the air
- Whirling air stream, due to the special air rectifier
- Double, turn able sprayer nozzles, adjustable in level, with non-drop-valve
- Solenoid valves with press regulations valve
- Large infuse opening with the hydraulic dust mixer at the basket filter
- Rotating tank washer
- Steering tow rod
- Lighting system

Additional equipment:

Electric valves, especially air deflectors, computers, spray control with sensors, lightning of nozzles with LED ...



PRIPOROČILO ZA UPORABO PRŠILNIKOV DT CR

- Medvrstna razdalja 2,0 - 4,5 m
- Višina škropljenja do 4,0 m
- Površina škropljenja
 - ZM 600 DT do 15 ha
 - ZM 800 DT do 15 ha
 - ZM 1000 DT do 20 ha
 - ZM 1500 DT do 25 ha
 - ZM 2000 DT do 25 ha
- Vrste nasadov
 - za moderne nasade v vertikalah



EINSATZBEREICH FÜR GEBLÄSESPRITZEN DT CR

- Reihenabstand 2,0 - 4,5 m
- Kulturhöhe bis 4,0 m
- empfohlene Sprühfläche
 - ZM 600 DT bis 15 ha
 - ZM 800 DT bis 15 ha
 - ZM 1000 DT bis 20 ha
 - ZM 1500 DT bis 25 ha
 - ZM 2000 DT bis 25 ha
- Anlagentyp
 - für moderne Anlagen in Vertikalen



USE RECOMMENDATIONS FOR SPRAYERS DT CR

- Row width 2,0 - 4,5 m
- Spraying height up to 4,0 m
- Recommended spraying area
 - ZM 600 DT up to 15 ha
 - ZM 800 DT up to 15 ha
 - ZM 1000 DT up to 20 ha
 - ZM 1500 DT up to 25 ha
 - ZM 2000 DT up to 25 ha
- Type of plantations
 - Only for verticals



Braglia



Zupan



Arag



Elmed



Inovel

											
	L	L/min	bar	Ø	m³/h	kW	N°	A mm	B mm	C mm	kg
ZM 600 DT CR-O (PE)	600	115	50	2 x 600	78000	27	14	1120	2088	2854	550
ZM 600 DT CR-O	600	115	50	2 x 600	78000	27	14	1070	2068	2880	560
ZM 800 DT CR-O (PE)	800	115	50	2 x 600	78000	27	14	1120	2088	3052	600
ZM 800 DT CR-O	800	115	50	2 x 600	78000	27	14	1070	2091	3050	610
ZM 1000 DT CR-O (PE)	1000	115	50	2 x 600	78000	27	14	1220	2160	3186	670
ZM 1000 DT CR-O	1000	115	50	2 x 600	78000	27	14	1220	2160	3115	685
ZM 1500 DT CR-O (PE)	1500	142	50	2 x 600	78000	28	14	1290	2228	3540	730
ZM 1500 DT CR-O	1500	142	50	2 x 600	78000	28	14	1220	2228	3444	740
ZM 2000 DT CR-O (PE)	2000	142	50	2 x 600	78000	28	14	1410	2248	3645	780
ZM 2000 DT CR-O	2000	142	50	2 x 600	78000	28	14	1360	2248	3645	790